



Water Meter Reading

Worldwide coverage

Leveraging off the wide spread deployment of modern Cellular Mobile Telephone Networks, and low cost mobile cell phone components CYPLEX has developed a scalable AMR solution with unmatched performance, convenience and reliability.

Seamless integration...

between gas, water and electricity meter reading and general monitoring applications. CYPLEX Networked Telemetry solution for AMR delivers instant billing data and site status information to a user's cell phone and to a utility's host computer almost anywhere in the world.

Fits to existing meters

The intrinsically safe design and the integrated long life battery allows the Packetiser to connect directly to any gas meter. High performance communications features provide reliable operation with meters in fringe signal areas.

2-way communications

The Packetiser meter interface unit provides reliable two-way communications using the now familiar packet data technology – SMS and GPRS – provided by cellular networks.

Program remotely

Packetiser is easily installed by non-technical personnel and then configured and managed from a utility's IT centre or an authorised engineer's laptop.

Low operating costs

Using proven data compression techniques developed by CYPLEX data transmission and air-time charges are reduced by 95% making Packetiser the most cost effective AMR device in the world.

Reliable in the toughest of environments

Packetiser for electricity works reliably in very low signal reception areas such as basements and within metal control panels without the need for an external antenna.



CYPLEX Communications

sales@cyplex.com.au
www.cyplex.com.au
Tel +61 2 9482 4269
Fax +61 2 9482 4222

CORPORATE OFFICES

SYDNEY - AUSTRALIA
38 Leighton Place
HORNSBY | NSW | 2077

SELANGOR - MALAYSIA
Suite W3/69, Wisma Widuri
JALAN KOSAS UTAMA,
68000 AMPANG
SELANGOR D.E

● Electricity

● Gas

● Water

Key Features

- On-line 24 hours per day
- Reprogrammable over the network
- 100% non-volatile memory storage for over 65 days of quarter hourly logged data
- Additional analogue / digital inputs and outputs for value added services
- Automatic time synchronisation to better than five seconds of real time
- Password protection to four levels of security
- Integrated tamper detection
- Data compression of up to 95% to minimise communication packets transmitted
- Automatic resetting of locked modems
- User-programmable alarm description text for SMS status messages
- User-programmable alarm recipient list of GSM phone numbers
- User-programmable alarm acknowledgment routines
- No need to replace back-up batteries (memory / real time clock)
- Automatic detection of a faulty input pulse stream – “broken wire”
- Compact size and internal antenna for reduced installation time and cost
- Supports GSM SMS / GPRS, CDMA and Globalstar LEO networks
- Additional I/O and serial ports are available for other applications
- Used for telemetry applications to monitor distribution network and assets
- Interfaces to any billing system
- Load Control - Comprehensive Logic Functions
- Calender/ Holiday Logic Functions inbuilt
- Network Tracking
- Retrofit Design with Zero Footprint
- IP68 environmental rating

Specifications

Inputs - Digital

2 x Digital Inputs - event, watchdog or pulse logging function - user configurable

1 x Digital Input - event, watchdog function - user configurable

- Fully isolated to 5.3kV, max volts 32 Vdc.
- Turn on voltage 2.9volts @ 0.66ma @25°C. Turn on time 3.0us
- Turn off voltage 2.5volt. Turn off time = 2.3us
- Can use NPN, PNP or voltage free contact.
- Internal +5Vdc supply is provided to drive the digital inputs.

Inputs - Analog

2 x Analog Inputs - user configurable as logging inputs and with four setpoint alarms

1 x Analog Input - user configurable with four setpoint alarms

- 0-4 VDC 0.1% Acc 4000 Graduations
- Compatible with 4-20mA, 1-5V and 0-10V sensors
- Convertible to Digital Inputs

Inputs - Internal

1 x Tamper alarm

1 x Back up battery voltage - user configurable setpoint alarm

1 x AC Supply Failure

Outputs

2 x Digital outputs - for load control or other user applications.

- Non-isolated,
- Max voltage 60vdc
- Max continuous drain current 500ma
- Max power dissipation 300mW
- Surge current 800ma

Optional 30 Amp disconnect mono-stable relay available for load control of hot water systems.

Power Supply

Integrated Cyplex long life intrinsically safe battery supply for up to 15 years service life depending on usage.

